

LONG LINEAR FEEDING SYSTEM EO KV-Z

Model: EO KV-Z080 | EO KV-Z160 | EO KV-Z240



ACCURATE

- Precision mechanics and high-tech materials for highest accuracy
- Compact precision linear motor

VERSATILE INSTALLATION



- Compact linear axis in horizontal design
- Individual customizable feed lengths
- Drive units near axis (e.g. in tooling)

VERSATILE USE

- Single or multi-motor axis
- Various tailor made clamping, gripping and guiding options
- Adaptable covers

MATERIAL


- Material thickness up to 1 mm or 4 mm
- Variable feed lengths
- Choice of two motor sizes



LONG ELECTRIC LINEAR FEEDING SYSTEM EO KV-Z



PERFORMANCE



Performance curves (examples)*

Loop weight / Number of moving clamps



0.5 kg / 1 Z

2 kg / 1 Z

10 kg / 1 Z

*Calculation basis: EZ KV-Z
Optimum opening angle
Z= standard gripper

TECHNICAL SPECIFICATIONS



MODEL	EO	KV-Z080	KV-Z160	KV-Z240
Band width max. (mm)		80	160	240
C: Infeed guide width max (mm)		81	161	241
B: Width of klamp (mm)		98	178	258
A: Device length EO KV 32/40/48/80		496 / 576 / 656 / 976		
Feed length with EO KV 32/40/48/80		180 / 260 / 340 / 660		
Infeed height (mm)		199		
Clamping opening (mm)		1 or 4		
Accuracy (mm)		± 0.02		
Nominal traction force		65 N		
Peak traction force		140 N		
Clamping force at 6 bar		300 N	600 N	900 N
Band cross-section (max. recommended)		50 mm²		

SWITZERLAND

Zehnder & Sommer AG
CH-3400 Burgdorf
info@zehndersommer.com
Tel +41 31 800 00 00

GERMANY

Zehnder & Sommer GmbH
DE-58452 Witten
info@zehndersommer.de
Tel +49 2302 981 60 30

zehndersommer.com
ZSswiss.com