

PRODUCT OVERVIEW LINEAR AND GRIPPER FEEDING SYSTEMS EZ & J



ZEHNDERSOMMER.COM



Edition 2025-01		Model name		Number of clamps or grippers		Pitch	Passage	Clamp	Device dimensions (mm)					Traction force		Clamping force		Ratio		Precision	Stroke rate	Material cross section				
		Model	Dimension	fix	moving	max. mm	width mm	opening mm	Infeed height	Height with clamps	Height with cover	Device depth	Device width		max. (N)		max. N (6 bar)		clamping/traction		+/- position	max. recommended	recommended (mm²)			
													body	total	nominal	peak	single clamp	max. clamps	single	doubleclamps	mm	strokes/minute	slow	fast		
EZL		EZL	220-072	1	1	72	220					280	260	260	110	200	640	-	++	-		500				
			100-085	1	1	84	100	1.0	76.5	94	100	292	140	145	100		290	-	+	-	0.01	600	100	50		
LINEAR FEED SMALL		EZ KL-C	080	1 (2)	1 (2)	50						180			60	100		540		-	0.02	600	40	25		
		EZ KL-D	080	1 (2)	1 (2,3)	64	81	1.0	76.5	93	100	310	112	121	65	140	270	810	++	+++	0.01	800	50	30		
		EZ KL-E	080	1 (2)	1 (2,3)	145							440								0.02	600				
		EZ KV-C	040	1	1	50							180			60	100		135		-	0.02	600	40	25	
		EZ KV-D	040	1 (2)	1 (2)	64	41	1.0	129.5	147	154	310	86	90	65	140	135	270		+	++	0.01	800	50	30	
		EZ KV-E	040	1 (2)	1 (2)	145							440									0.02	600			
		EZ KT-D	080		2 (4)	2x48	81	1.0	76.5	93	100	310	112	121	65	140	270	540	++	+++	0.02	1200	50	30		
		EZ KX-C	080		2	2x28							180			60	100				++	-	0.03	1000	40	25
EZ KX-D	080		2	2x85	81	1.0	129.5	147	154	310	116	125	65	140	310	-			++	-	0.02	1200	50	30		
LINEAR FEED MEDIUM		EZ ML-C	160	1 (2)	1 (2)	45	161	1.0	76.5	93	100	310	192	201	180	300	540	1080	+	++	0.03	800	150	80		
		EZ ML-D	160	1 (2)	1 (2)		161						192	201	200	450	540	1080	+	++	0.01	1000	200	100		
			240	1 (2)	1 (2)	100	241	1.0	76.5	93	100	310	272	281	200	450	900	1800	++	+++		800				
		EZ ML-E	160	1 (2)	1 (2)		161						192	201	200	400	540	1080	+	++	0.02	800	200	100		
			240	1 (2)	1 (2)	145	241	1.0	76.5	93	100	440	272	281	200	400	900	1800	++	+++		600				
		EZ MV-D	080	1 (2)	1 (2)	102				209.5			310								++	+++	0.02	800	200	100
		EZ MV-E	080	1 (2)	1 (2)	145	81	1.0	209.5	227	236	440	116	125	200	450	1100	2200		++	+++					
		EZ MX-D	080-120		2	2x60							310			200	450	1100	-	++	-	0.02	1200	200	100	
EZ MX-D	080-200		2	2x100	85	1.0	209.5	227	234	350	125	125	220	450	1100	-	++	-	0.02	1000	200	100				
J 380		J 380	.030	1	1	33	64					262									0.01	300	80			
			.060	1	1	66	64	1.4	39	48	53	328	78	82			580	-	+	-		250				