


ELECTRICAL GRIPPER FEED **EZ KL 80**

Models: EZ KL-C 80 | EZ KL-06 80 | EZL KL-14 80



ACCURATE



- Precision mechanics and high-tech materials for highest accuracy
- Compact precision linear motor

VERSATILE INSTALLATION

- Compact horizontal design with minimal installation height
- Available in 3 unit lengths
- Cable Connector Box: separate or on device (KL-C)
- Variable infeeds: basket with double rolls, inlet plate, wire inlet

VERSATILE USE

- Prepared for additional clamps, better wire guiding, considerable clamping force
- Various tailor made clamping, gripping and guiding options
- Good visibility into gripper chamber for easy threading
- Threading help button (material insertion without operating the control)
- Adaptable roll basket to fit material properties




**ZEHNDER
SOMMER** | SWISS
PRECISION
FEEDING

ELECTRICAL GRIPPER FEED EZ KL 80



PERFORMANCE



Performance curves (examples)*

Loop weight / Number of moving clamps

0 kg / 1 clamp

0.5 kg / 1 clamp



2 kg / 1 clamp

0.5 kg / 2 clamp

2 kg / 2 clamp

*Calculation basis: EZ KL-06 80
Optimum opening angle

TECHNICAL SPECIFICATIONS



MODEL	EZ	KL-C 80	KL-06 80	KL-14 80
Bandwidth max. (mm)		80		
Feed length max. (mm)		50	60	140
A:Length basic unit (mm)		180	260	420
B:Length with inlet plate (mm)		210	290	450
C:Length with roll basket type D (mm)		311	391	551
Clamp opening		ca. 1 mm		
Accuracy (mm)		+/- 0.02	+/- 0.01	+/- 0.01
Nominal traction force (N)		45	68	68
Peak traction force, approx. (N)		100	150	150
Clamping force at 6 bar (movable gripper)		(1) 270 N / (2) 540 N		
Cross section (recommended)		max. 50 mm ²		

SWITZERLAND

Zehnder & Sommer AG
CH-3400 Burgdorf
info@zehndersommer.com
Tel +41 31 800 00 00

GERMANY

Zehnder & Sommer GmbH
DE-58452 Witten
info@zehndersommer.de
Tel +49 2302 981 60 30

zehndersommer.com
ZSswiss.com